



USER MANUAL

HDMI Extender over single CAT5E/6 60M

Model: LM-EX11B

1、 Introduction

LM-EX11B Used for a pair extension of this HDMI CAT 5e / 6 cable to extend HD signal up to 60 meters, and can achieve 1080P, which not only broke the HDMI cable transmission length limitations, but also more convenient and flexible, the majority of customers are more cost savings. The production equipment company providing solutions for the following applications: such as noise, limited transmission distance and safety of the place, data center control, information distribution, conference room presentations and teaching environment and corporate training sites.

Our devices offers solutions for noise, space and security concerns, data center control, information distribution, conference room presentation, school and corporate training environments.

2、 FEATURES

- Support HDMI 1.3 protocol
- HDCP 1.2 protocol compliant
- Support 3D
- Support video input : 24/50/60fs/1080p/1080i/720p/576p/576i/480p/480i
- Signal transmission: Single cat-6e or cat-6(recommended) cable up to 60 meters
- Support video output : 24/50/60fs/1080p/1080i/720p/576p/576i/480p/480i
- Audio format support : DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD.
- Support up to 5metres AWG26 cable length between extender and source & sink device
- No loss of quality

3、 SPECIFICATIONS

Length of CAT-5E or CAT-6 cable between Rx and TX	Up to 60 meters
HDMI Input	24/50/60fs/1080p/1080i/720p/576p/576i/480p/480i
Support audio format input	DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD
HDMI Output	24/50/60fs/1080p/1080i/720p/576p/576i/480p/480i
Support audio format output	DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD
Max transmission bandwidth	5.1Gbps
Input Video signal	0.5~1.5Volts p-p
Output DDC signal	5Volts p-p (TTL)
Input/Output HDMI1.3 cable distance	≤20m AWG26 HDMI 1.3 standard cable
Max working current	400mA
Power adapter format	Input:AC (50HZ, 60HZ) 100V-240V; Output: DC5V/1 A
Operating Temperature range	(-15 to +55℃)
Operating Humidity range	5 to 90%RH (No Condensation)
Dimension (L x W x H)	82X45X21 (mm)
Weight	220g

4、 Package Contents

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- 1) Main unit No. 1 Sender
- 2) Main unit No. 2 Receiver
- 3) Two pieces of 5V DC Power Supply.
- 4) User' s Manual

5、 CONNECTING AND OPERATING

- 1、 Connect one HDMI 1.3 cable up to 20 meters between source device and TX Extender.
- 2、 Connect one HDMI 1.3 cable up to 20 meters between sink device and RX Extender
- 3、 Connect single cat-5e or cat-6(recommended) cables up to 60 meters instead of HDMI cable between TX and RX Extender
- 4 、 Connect 5V power supply to the HDMI CAT60RX&TX Extender

